



FLANGE WELDING NECK FORGIATE

ASME B 16.5 ASTM A182
SCH 40S
ASTM A 105
ASTM A 403
150 / 300 / 600 LBS

FORGED WELDING NECK FLANGES

ASME B 16.5 ASTM A182
SCH 40S
ASTM A 105
ASTM A 403
150 / 300 / 600 LBS

STAINLESS STEEL AND CARBON STEEL

300 LBS

Nom. Size	O.D. mm	D mm	J mm	b mm	h mm	a mm	m mm	g mm	l mm	k mm	Fori Holes	kg
1/2"	21.3	95	15.7	14.2	51	21.3	38.1	35.0	15.7	66.7	4	0.75
3/4"	26.7	115	20.8	15.7	56	26.7	47.7	42.9	19.0	82.6	4	1.26
1"	33.4	125	26.7	17.5	60	33.5	53.8	50.8	19.0	88.9	4	1.52
1 1/4"	42.2	135	35.1	19.0	64	42.2	63.5	63.5	19.0	98.4	4	2.03
1 1/2"	48.3	155	40.9	20.6	67	48.3	69.5	73.1	22.3	114.3	4	2.89
2"	60.3	165	52.6	22.3	67	60.4	84.0	91.9	19.0	127.0	8	3.40
2 1/2"	73.0	190	62.7	25.4	75	73.1	100.0	104.6	22.3	149.2	8	5.17
3"	88.9	210	78.0	28.4	78	88.9	117.3	127.0	22.3	168.3	8	6.93
4"	114.3	255	102.4	31.7	84	114.3	146.0	157.2	22.3	200.0	8	11.20
5"	141.3	280	128.3	35.1	97	141.3	177.8	185.7	22.4	235.0	8	15.10
6"	168.3	320	154.2	36.5	97	168.4	206.2	215.9	22.3	269.7	12	19.10
8"	219.1	380	202.7	41.1	110	219.2	260.3	269.7	25.4	330.2	12	29.90
10"	273.0	445	254.5	47.6	116	273.1	320.7	323.8	28.6	387.3	16	44.30
12"	323.8	520	304.8	50.8	129	323.9	374.6	381.0	31.7	450.8	16	64.00

SCH 10S/80S SU RICHIESTA / ON REQUEST

600 LBS

Nom. Size	D mm	J mm	b mm	h mm	a mm	m mm	g mm	l mm	k mm	Fori Holes	kg
1/2"	95	15.7	14.2	52	21.3	38.1	35.0	15.7	66.7	4	0.90
3/4"	115	20.8	15.7	57	26.7	47.7	42.9	19.0	82.6	4	1.50
1"	125	26.7	17.5	62	33.5	53.8	50.8	19.0	88.9	4	1.90
1 1/4"	135	35.1	20.6	67	42.2	63.5	63.5	19.0	98.4	4	2.60
1 1/2"	155	40.9	22.2	70	48.3	69.5	73.1	22.2	114.3	4	3.30
2"	165	52.6	25.4	73	60.4	84.0	91.9	19.0	127.0	8	4.70
2 1/2"	190	62.7	28.6	79	73.1	100.0	104.6	22.2	149.2	8	6.50
3"	210	78.0	31.7	83	88.9	117.3	127.0	22.2	168.3	8	8.70
4"	275	102.4	38.1	102	114.3	152	157.2	25.4	215.9	8	18.1
5"	330	128.3	44.4	11	141.3	189	185.7	28.6	266.7	8	30.5
6"	355	154.2	47.6	117	168.4	222	215.9	28.6	292.1	12	36.2
8"	420	202.7	55.6	133	219.2	273	269.7	31.7	349.2	12	56.5
10"	510	254.5	63.5	152	273.1	343	323.8	34.9	431.8	16	91.0
12"	560	304.8	66.7	156	323.9	400	381.0	34.9	488.9	20	105

SCH 10S/80S SU RICHIESTA / ON REQUEST

150 LBS

Nom. Size	O.D. mm	D mm	J mm	b mm	h mm	a mm	m mm	g mm	l mm	k mm	Fori Holes	kg
1/2"	21.3	90	15.7	11.2	46	21.3	30	35.1	15.7	60.3	4	0.48
3/4"	26.7	100	20.8	12.7	51	26.7	38	42.9	15.7	69.9	4	0.71
1"	33.4	110	26.7	14.2	54	33.5	49	50.8	15.7	79.4	4	1.01
1 1/4"	42.2	115	35.1	15.7	56	42.2	59	63.5	15.7	88.9	4	1.33
1 1/2"	48.3	125	40.9	17.5	60	48.3	65	73.2	15.7	98.4	4	1.72
2"	60.3	150	52.6	19.1	62	60.5	78	91.9	19.1	120.7	4	2.58
2 1/2"	73.0	180	62.7	22.4	68	73.2	90	104.6	19.1	139.7	4	4.11
3"	88.9	190	78.0	23.9	68	88.9	108	127.0	19.1	152.4	4	4.92
4"	114.3	230	102.4	23.9	75	114.3	135	157.2	19.1	190.5	8	6.84
5"	141.3	255	128.3	23.9	87	141.2	164	185.7	22.4	215.9	8	9.20
6"	168.3	280	154.2	25.4	87	168.4	192	215.9	22.4	241.3	8	10.60
8"	219.1	345	202.7	28.4	100	219.2	246	269.7	22.4	298.5	8	17.60
10"	273.0	405	254.5	30.2	100	273.1	305	323.9	25.4	362.0	12	24.00
12"	323.8	485	304.8	31.8	113	323.9	365	381.0	25.4	431.8	12	36.50
14"	355.6	535	336.5	34.9	125	355.6	400	412.7	28.6	476.2	12	51.00
16"	406.4	595	387.3	36.5	125	406.4	457	469.9	28.6	539.8	16	60.00
18"	457.2	635	438.1	39.6	138	457.2	505	533.4	31.8	577.9	16	68.30
20"	508.0	700	488.9	42.9	143	508.0	559	584.2	31.8	635.0	20	84.50
24"	609.6	815	590.5	47.8	151	609.6	663	692.2	35.1	749.3	20	115.00

SCH 10S/80S SU RICHIESTA / ON REQUEST